

Hebron Ventures Inc. & Hebron Ventures North America



Product – Electric Car



Brief Profile

Hebron Ventures is a North American business with hubs in the United States & Canada. Hebron Ventures imports products from Far East & South East Asian countries.

We would like to introduce one of our main products – E- Cars.

Model	Item	Specification	Picture		
YMJ-L606	electric 6 passenger classic car	Battery: 8pcs*6V/pc220AH Motor: 48V 4.2KW DC series excitation Max. Speed (km/h): 35-40 Max. Range(km): 80-100 Max. Climbing capacity: 15-20% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4700×1680×1960 Unloading weight(kgs): 1300 Passenger capacity: 6 persons Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-L608	electric 8 passenger classic car	Battery: 8pcs*6V/pc220AH Motor: 48V 4.2KW DC series excitation Max. Speed (km/h): 35-40 Max. Range(km): 80-100 Max. Climbing capacity: 15-20% Min. Grounding distance (mm): ≥ 150 Dimensions: 5200×1680×1960 Unloading weight(kgs): 1400 Passenger capacity: 8 persons Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-J604B	electric car	Battery: 8pcs* 6V/pc220AH Motor: 48V4.2kW DC series excitation Max. Speed (km/h): 40-45 Max. Range(km): 80-100 Max. Climbing capacity: 15-25% Min. Grounding distance (mm): ≥ 150 Dimensions: 4310mm×1460mm×1720mm Unloading weight(kgs): 950 Passenger capacity: 4 persons doors: optional Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-T25	Electric animal car	Battery: 12pcs*6V/pc220AH, Motor:72v 6.3KW DC series excitation Max. Speed (km/h): 30-40km/h Max. Range(km): 80 Max. Climbing capacity: 10% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 6500*1620*2230 Unloading weight(kgs): 2000 Passenger capacity:18 persons Qty in Container: 1unit/40HQ			
YMJ-A619	Electric touring bus	Battery: 12pcs*6V/pc220AH, Motor:72v 6.3KW DC series excitation Max. Speed (km/h): 30-40km/h Max. Range(km): 80-100 Max. Climbing capacity: 10% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 6300*1620*2100 Unloading weight(kgs): 2000 Passenger capacity:19 persons with rear cargo box Qty in Container: 1unit/40GP			
YMJ-608	Electric touring bus	Battery:8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3700×1460×2100 Unloading weight(kgs): 900 Passenger capacity: 8 persons Qty in Container: 1unit/20GP, 3units/40GP			

YMJ-606	Electric touring bus	Battery: 8pcs*6V/pc220AH Motor: 48v 3KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3000x1220x1850 Unloading weight(kgs): 820 Passenger capacity: 6 persons Qty in Container: 2unit/20GP, 4units/40GP			
YMJ-J604	Electric patrol car	Battery: 8pcs*6V/pc220AH Motor: 48v 3KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3000x1220x1850 Unloading weight(kgs): 820 Passenger capacity: 4 persons Qty in Container: 2unit/20GP, 4units/40GP			
YMJ-N608	new electric tourist bus	Battery: 8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3700x1460x2100 Unloading weight(kgs): 900 Passenger capacity: 8 persons Qty in Container: 1unit/20GP, 3units/40GP			
YMJ-N611	new electric tourist bus	Battery: 12pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4080x1460x2100 Unloading weight(kgs): 1120 Passenger capacity: 11 persons Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-N614	new electric tourist bus	Battery: 12pcs*6V/pc220AH Motor: 72V 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15-20% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4810x1460x2100 Unloading weight(kgs): 1250 Passenger capacity: 14 persons Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-T13-CM	Electric city bus	Battery: 12pcs*6V/pc210AH Motor: 72V 5.5KW DC series excitation Max. Speed (km/h): 35-40 Max. Range(km): 80-100 Max. Climbing capacity: 10-15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4400x1550x2000 Unloading weight(kgs): 1200 Passenger capacity: 13 persons Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-T17-CM	Electric city bus	Battery: 12pcs*6V/pc210AH Motor: 72V 6.3KW DC series excitation Max. Speed (km/h): 35-40 Max. Range(km): 80-100 Max. Climbing capacity: 10-15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4800x1550x2450 Unloading weight(kgs): 1350 Passenger capacity: 17 persons Qty in Container: 1unit/20GP, 2units/40GP			

YMJ-J604A	Electric ambulance	Battery:8pcs*6V/pc220AH Motor: 4KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3000×1220×1850 Unloading weight(kgs): 820 Passenger capacity: 5persons Qty in Container: 2unit/20GP,4units/40GP			
YMJ-J606A	Electric ambulance	Battery:8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3700×1460×2100 Unloading weight(kgs): 920 Passenger capacity: 7 persons Qty in Container: 1unit/20GP,3units/40GP			
YMJ-T4	Electric closed ambulance	Battery:8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3700×1460×2100 Unloading weight(kgs): 920 Passenger capacity: 5 persons Qty in Container: 1unit/20GP, 3units/40GP			
YMJ-X604	Electric fire engine	Battery:8pcs*6V/pc190AH Motor: 48v 3KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3000×1220×1850 Unloading weight(kgs): 820 Passenger capacity: 2 persons Qty in Container: 2unit/20GP,4units/40GP			
YMJ-T11	Electric fire engine	Battery:8pcs*6V/pc190AH Motor: 48v 3KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3000×1220×2100 Unloading weight(kgs): 700 Passenger capacity: 2 persons Qty in Container: 2unit/20GP,4units/40GP			
YMJ-T38	Electric van	Battery:12pcs*6V/pc220AH Motor:4.2KW DC series excitation Max. Speed (km/h): 35-40 Max. Range(km): 80-100 Max. Climbing capacity: 10% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3800*1420*2020 Unloading weight(kgs): 1250 Max loading weight(kgs): 1000kgs Qty in Container: 1unit/20GP,3units/40GP			
YMJ-T7	Electric van	Battery:8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4300×1550×2020 Unloading weight(kgs): 800 Max loading weight: 1000kgs Qty in Container: 1unit/20G, 2units/40GP			

YMJ-H602	Electric truck	Battery: 8pcs*6V/pc220AH Motor: 3KW DC series excitation Max. Speed (km/h): 30-35 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 4300×1550×2030 Max loading weight: 1000kgs Unloading weight(kgs): 800 Qty in Container: 1unit/20GP, 2units/40GP			
YMJ-T55	Electric industrial car	Battery: 8pcs*6V/pc220AH Motor: 4.2KW DC series excitation Max. Speed (km/h): 30-40 Max. Range(km): 80-100 Max. Climbing capacity: 15% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 3700×1460×2100 Unloading weight(kgs): 800 Passenger capacity: 8 persons Qty in Container: 1unit/20GP, 3units/40GP			
YMJ-T40	Three wheel motorcycle	Battery: 4pcs*12V/pc20AH Motor: 500W DC series excitation Max. Speed (km/h): 25km/h Max. Range(km): around 40 Max. Climbing capacity: 10% Dimensions(mm): 2620*1130*1230 Unloading weight(kgs): 167 Max loading weight(kgs): 250 Qty in Container: 4unit/20GP, 16units/40HQ			
YMJ-T35	Electric mini car	Battery: 2pcs*12V/pc120AH Motor: 24V350WDC Speed (km/h): 5-7km/h Max. Range(km): around 80 Max. Climbing capacity: 10% Min. Grounding distance (mm): ≥ 150 Dimensions(mm): 1155×1350×1680 Unloading weight(kgs): 200 Qty in Container: 8unit/20GP, 16units/40GP	Max. 		

Contact Us

USA

1009 KENSINGTON BLVD,
FORTWAYNE , IN - 46805

Tel: +1260-437-7733

Rev. William CP B.Eng, MBA

revwillcp7@gmail.com

Canada

70 Borden Avenue South, Kitchener, Ontario N2G-3R5

Rev. William CP B.Eng, MBA

Tel: +1 226 338 1594

revwillcp7@gmail.com

Richard Herrfort

Tel: +1-226-791-4533

Email : rickht77@gmail.com

George Thomas

Tel: +1 519 501 7723

Email: callmrgs@gmail.com