

HEBRON VENTURES INC.

HEAD SET , EAR PHONE

No.	Model No.	Image	Specifications
1	TP-EH-S488		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:105±3dB(1KHz,10mW) Rated input power:25mW Maximum input power:40mW R&L balances≤3dB(50Hz-5KHz) Cable:1.5M PVC material plug:ø3.5mm 3P gold plated Mic Sensitivity:4015 -42±3dB
2	TP-EH-S452		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:105±3dB(1KHz,10mW) Rated input power:25mW Maximum input power:40mW R&L balances≤3dB(50Hz-5KHz) Cable:1.2M PVC material plug:ø3.5mm 3P gold plated Mic Sensitivity:4015 -42±3dB
3	TP-EH-S458		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:105±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz) Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 4P gold plated Cable:1.2M TPE material
4	TP-EP-J232		Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz) Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 3P gold plated Cable:1.2M TPE material
5	TP-EP-J225		Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:103±3dB(1KHz,10mW) Rated input power:5mW Maximum input power:10mW R&L balances≤3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.2M TPE material
6	TP-EP-J20A		Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.2M TPE material
4	TP-EH-S468		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz) Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 3P gold plated Cable:1.25M TPE material
5	TP-EH-S469		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:103±3dB(1KHz,10mW) Rated input power:5mW Maximum input power:10mW R&L balances≤3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.25M TPE material
6	TP-EH-U477		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.25M TPE material
1	TP-EH-S402		Driver size:ø40mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:105±3dB(1KHz,10mW) Rated input power:25mW Maximum input power:40mW R&L balances≤3dB(50Hz-5KHz) Cable:1.8M PVC material plug:ø3.5mm 3P gold plated Mic Sensitivity:4015 -42±3dB
3	TP-EP-J210		Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:105±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances≤3dB(50Hz-5KHz)

			<p>Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 4P gold plated Cable:1.25M TPE material</p>
4	TP-EP-J212		<p>Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances±3dB(50Hz-5KHz) Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 3P gold plated Cable:1.25M TPE material</p>
5	TP-EP-J259		<p>Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:103±3dB(1KHz,10mW) Rated input power:5mW Maximum input power:10mW R&L balances±3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.25M TPE material</p>
6	TP-EP-J260		<p>Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances±3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.25M TPE material</p>
7	TP-EP-J278		<p>Driver size:ø9mm Frequency response:20Hz~20KHz Impedance:16 Ohm Sensitivity:95±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances±3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.2M TPE material</p>
8	TP-EP-J279		<p>Driver size:ø8mm Frequency response:20Hz~20KHz Impedance:16 Ohm Sensitivity:94±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances±3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.2M TPE material</p>
9	TP-EP-P16		<p>Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:32 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:5mW Maximum input power:10mW R&L balances±3dB(50Hz-5KHz) Mic Sensitivity:4015 -42±3dB plug:ø3.5mm 4P gold plated Cable:1.25M TPE material</p>
10	TP-EP-J275		<p>Driver size:ø10mm Frequency response:20Hz~20KHz Impedance:16 Ohm Sensitivity:98±3dB(1KHz,10mW) Rated input power:3mW Maximum input power:5mW R&L balances±3dB(50Hz-5KHz) plug:ø3.5mm 4P gold plated Cable:1.2M TPE material</p>